


A

Express Mail Label No. EJ217839063US

UTILITY PATENT APPLICATION TRANSMITTAL <small>(Only for new nonprovisional applications under 37 CFR 1.53(b))</small>		Attorney Docket No. ABS-001 (242/2)	
		First Named Inventor Ran Oz	
		Title USING DELAY TIME	

APPLICATION ELEMENTS	ADDRESS TO: Box Patent Application Assistant Commissioner for Patents Washington, D.C. 20231
1. <input type="checkbox"/> Fee Transmittal Form	ACCOMPANYING APPLICATION PARTS
2. <input checked="" type="checkbox"/> Specification and Drawings [Total Pages 26] Specification - (15 pages) Claims - (5 pages) Abstract - (1 page) Sheets of Drawings - (5 sheets) <input type="checkbox"/> Formal <input checked="" type="checkbox"/> Informal	
3. <input type="checkbox"/> Oath or Declaration [Total Pages] a. <input type="checkbox"/> Newly executed (original) b. <input type="checkbox"/> Copy from a prior application (37 CFR 1.63(d)) <i>(for continuation/divisional with Box 17 completed)</i> <i>[Note Box 4 below]</i>	
4. <input type="checkbox"/> Incorporation by Reference (usable if Box 3b is checked) The entire Disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 3b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.	7. <input type="checkbox"/> 37 CFR 3.73(b) Statement (when there is an assignee) <input type="checkbox"/> Power of Attorney
5. <input type="checkbox"/> Microfiche Computer Program (<i>Appendix</i>)	8. <input type="checkbox"/> English Translation Document (<i>if applicable</i>)
6. <input type="checkbox"/> Nucleotide and/or Amino Acid Sequence Submission <input type="checkbox"/> Computer Readable Copy <input type="checkbox"/> Paper Copy (identical to computer copy) <input type="checkbox"/> Statement verifying identity of above copies	9. <input type="checkbox"/> Information Disclosure Statement (IDS)/PTO-1449 <input type="checkbox"/> Copies of IDS Citations
17. <input type="checkbox"/> If a CONTINUING APPLICATION, check appropriate box and supply the requisite information: <input type="checkbox"/> Continuation <input type="checkbox"/> Divisional <input type="checkbox"/> Continuation-in-part (CIP) of prior application Serial No. . Priority to the above application(s) is claimed under 35 U.S.C. 120. Prior application information: Examiner: . Group/Art Unit: .	10. <input type="checkbox"/> Preliminary Amendment <input type="checkbox"/> Drawings [Total Sheets] <input type="checkbox"/> Letter to Official Draftsperson Including Drawings [Total Pages]
18. <input checked="" type="checkbox"/> Priority - 35 U.S.C. 119 <input checked="" type="checkbox"/> Priority of application Serial No. <u>60/122,437</u> filed on <u>March 2, 1999</u> is claimed under 35 U.S.C. 119. <input type="checkbox"/> The certified copy has been filed in prior U.S. application Serial No. ____ / ____ on ____. <input type="checkbox"/> The certified copy will follow.	11. <input checked="" type="checkbox"/> Return Receipt Postcard
	12. <input type="checkbox"/> Small Entity Statement(s) <input type="checkbox"/> Statements filed in prior application, (Status still proper and desired)
	13. <input type="checkbox"/> Certified Copy of Priority Document(s)
	14. <input type="checkbox"/> Deletion of Inventor(s) Signed statement attached deleting inventor(s) named in the prior application.
	15. <input checked="" type="checkbox"/> Patent Application Data Entry Form
	16. <input type="checkbox"/> Other:

CORRESPONDENCE ADDRESS	SIGNATURE BLOCK
Direct all correspondence to: Patent Administrator Testa, Hurwitz & Thibault, LLP High Street Tower 125 High Street Boston, MA 02110 Tel. No.: (617) 248-7000 Fax No.: (617) 248-7100	Date: March 2, 2000 Reg. No. 35,393 Tel. No.: (617) 248-7374 Fax No.: (617) 248-7100 <div style="text-align: right;">Respectfully submitted,  Robert J. Tosti Attorney for Applicants Testa, Hurwitz & Thibault, LLP High Street Tower 125 High Street Boston, MA 02110 </div>

GIANNETTA242/2.953100 -1

Inventor Information

Inventor One Given Name :: Ran
Family Name :: Oz
Postal Address Line One :: 27 Nahal Gaaton Street
City :: Modiin
State/Province ::
Country :: ISRAEL
Postal or Zip Code :: 71700
City of Residence :: Modiin
State/Prov. of Residence ::
Country of Residence :: ISRAEL
Citizenship :: ISRAEL

Inventor Two Given Name :: Amir
Family Name :: Bassan-Eskenazi
Postal Address Line One :: 2820 Juniper Street
City :: San Mateo
State/Province :: CA
Country :: U.S.A.
Postal or Zip Code :: 94403
City of Residence :: San Mateo
State/Prov. of Residence :: CA
Country of Residence :: U.S.A.
Citizenship :: ISRAEL

Correspondence Information

Correspondence Customer Number :: 021323

Application Information

Title Line One :: Using Delay Time
Title Line Two ::
Total Drawing Sheets :: 5
Formal Drawings :: NO
Application Type :: Utility
Docket Number :: ABS-001
Licensed - U S Government Agency ::
Contract Number ::
Grant Number ::
Secrecy Order in Parent Application ::

Representative Information

Representative Customer Number :: 021323

Priority Information

This application claims :: priority to and the benefit of U.S. provisional patent application serial no. 60/122,437 filed on March 2, 1999.
BEHRAKIS242/2.953034-1

USING DELAY TIME

Cross-Reference to Related Case

This claims priority to and the benefit of U.S. provisional patent application serial
5 number 60/122,437, filed on March 2, 1999.

Technical Field

The invention relates generally to displaying information on a screen. More
particularly, the invention relates to displaying information during a period of delay when
switching between channels.

Background Information

Television broadcasters and transport companies, such as cable companies or
Digital Broadcast Satellite (DBS) companies, transmit media streams to a customer's
receiver for subsequent display on a display screen of, for example, a television. The
receiver typically is separate from, but coupled to, the television or other device having
15 the display screen. The receiver can be capable of receiving media streams containing
compressed digital programs in the MPEG-2 format, and such a receiver typically is
referred to as a digital set-top box (STB). In general, a system supporting the
transmission and reception of digital media streams includes a server computer (located,
for example, at a cable headend) and "thin-client" that runs software on a customer's

digital STB. The server and the digital STB typically communicate via a two-way network, but they also can communicate to a limited extent via a one-way network.

Summary of the Invention

5 The use of a digital STB introduces at least a one to two second delay time when a customer switches from one channel to another, and this delay time is due to channel tuning time, MPEG transport parsing initialization, and MPEG program internal structure. The delay time occurs, for example, when a viewer specifies a new channel number or presses the up/down arrows on a remote control coupled to the digital STB.

10 There also is a delay associated with the thin-client displaying an electronic program guide in response to a customer or viewer request for the guide. The guide enables the viewer to view information on the various programs available on the various channels before selecting a preferred program. Although any delay time is typically in the order of one to two seconds, it can increase when a new program is added to a channel by the

15 cable headend, such that a two to four second delay occurs. Basically, it takes a few seconds for a decoder in the digital STB to process a new media stream before displaying the multimedia presentation contained within the stream. These types of digital STB-related or digital STB-introduced delays generally are referred to hereinafter as “zap time.” During zap time, the viewer sees small squares (blocks) of the target video

20 program being overlaid on top of the prior video program on the screen, until the prior video program is fully replaced with the target video program.

The invention relates to methods and systems for displaying data to the viewer during zap time. This displayed data can include, for example, one or more of the following: advertising; information about the next/target program or channel selected; a window showing a segment of the target program that is transmitted over the target channel; personal information associated with the viewer (e.g., notification that one or more electronic mail messages have arrived, stock prices of securities in the viewer's portfolio, etc.) and/or based on the viewer's profile (e.g., recipes for cooking enthusiasts, news clips from preferred sources, advertisements of particular interest, etc.); and local and regional information (e.g., weather forecasts, etc.). The displayed data also can include interactive elements that allow the viewer to request additional data for display on the screen. In addition, the interactive elements can correspond to a one-way transaction, such as when modifying the viewer's profile to block certain types of data. The data displayed during zap time generally is referred to hereinafter as a "zap page."

The zap page is pre-rendered and stored within the memory and/or buffer of the digital STB. When the viewer requests a switch in channels, such as by selecting a channel number or pressing a channel selection arrow on a remote control, the zap page is displayed substantially immediately. The zap page is displayed until the channel switch has been completed and then the target program is displayed in place of the zap page. However, if the viewer engages in or is engaged in an interactive session related to one or more interactive elements displayed on the zap page, the display of the target program is suspended until the viewer disengages the interactive session by sending a resume signal to the digital STB (such as by pressing a certain button on the remote control).

In one embodiment, a server periodically multicasts zap page contents to a plurality of viewers. A receiver, such as a digital STB, selects one of the plurality of zap pages and stores it in the buffer of the digital STB until a zap event is received that triggers the transmission and display of that zap page on the screen. The digital STB can also select and store one or more of the plurality of zap pages in the buffer and/or other memory of the digital STB so that when the “current” zap page stored in the buffer is displayed, one of the other zap pages can be transferred to the buffer in preparation for future transmission and display on the screen. Executable code stored within the memory of the digital STB and executed by a processor in the digital STB controls the selection, storage, and display of the zap page. When selecting one of the plurality of zap pages transmitted by the server, the executable code can select the first zap page received after a prior zap page has been displayed or it can select the zap page based on viewer profile information that it has gathered or that has been provided by the server. Alternatively, the server can narrow cast zap pages of a particular type to an individual viewer based on that viewer’s profile information. The profile information can be obtained from the digital STB, assimilated by the server itself, and/or this profile information can be accessed from another data source such as a database accessible via the Internet or other communications network.

When the viewer engages in an interactive session, the additional data can be obtained from local storage or memory located in, or associated with, the digital STB or it can be obtained from the server. If the transaction requested in the interactive session requires an interface with an external transaction provider, the digital STB can transmit

the request to the server for further processing. The server would then service this request by obtaining the data from the appropriate transaction provider and subsequently forwarding it back to the digital STB for display on the screen.

Although aspects of this invention are, at least in part, related to cable television systems (and, more particularly, to digital cable television systems), the invention can be applied to other types of broadcasting and transport systems (e.g., digital broadcast satellites, telephone systems, etc.). Aspects of this invention can also be applied to packet networks such as the Internet. For example, zap page content can be displayed in a web browser during the delay period between requesting an HTML page and receiving that HTML page. Zap page content can also be displayed during the delay period between launching the execution of a software application (such as a compute intensive or graphic-rendering application) and receiving the output/results of that launched software application.

In one aspect, the invention features a method of displaying data. The method comprises storing a first data set, such as a zap page. The method further comprises receiving a request to display a second data set, such as when a digital STB receives a signal from a remote control device to switch channels and display another program. The method further comprises receiving the requested second data set, which can then be transmitted to a display device. The method also comprises transmitting the first data set (to, for example, the display device) during a delay period between receiving the request and receiving the second data set.

In another aspect, the invention relates to a system for displaying data. The system includes a buffer, an input element, a network interface, a display device, memory storing executable code, and a processor. The buffer stores a first data set, such as a pre-rendered zap page. The input element receives a request for a second data set, such as when a digital STB receives a signal from a remote control device to display a program on another channel. The network interface receives the second data set from, for example, a server at a cable headend. The display interface transmits data to a display device, such as a television screen. The memory stores the executable code that, for example, monitors and/or controls at least part of the operation of the system. The processor executes the executable code in response to the request received by the input element. The executable code instructs the display interface to transmit the first data set in the buffer to the display device during a delay period between receiving the request and receiving the second data set.

The foregoing and other objects, aspects, features, and advantages of the invention will become more apparent from the following description and from the claims.

Brief Description of the Drawings

In the drawings, like reference characters generally refer to the same parts throughout the different views. Also, the drawings are not necessarily to scale, emphasis instead generally being placed upon illustrating the principles of the invention.

Figure 1 illustrates an external environment to which a digital set-top box (STB) communicates, in accordance with the invention.

Figure 2 is a block diagram of internal components of the digital STB shown in Figure 1.

Figure 3 shows an example of a zap page that can be displayed on a display device, in accordance with the invention.

5 Figure 4 is a flow diagram of a process that displays a zap page during a delay period or zap time, in accordance with the invention.

Figure 5 is a more detailed process flow diagram than the diagram of Figure 4.

Description

10 Referring to Figure 1, the elements supporting the operation of the invention include a server 102, a data source 114, a network 104, a receiver 106, a display device 108, an input device 112, and a viewer 110 (a person or multiple people) of the display device 108. The server 102 can comprise a plurality of server computers as well as the software operating therein to provide, for example, video on demand, music on demand,
15 interactive MPEG, Internet access, telephony gateways, transaction processing, viewer profiling, selection/formation of zap page contents, etc. In performing these functions, the server 102 can access the data source 114 to obtain the desired data when necessary.

In one embodiment, the data source 114 corresponds to a data repository located on a local hard disk drive or other direct access storage device. In another embodiment,
20 the data source 114, corresponds to a database or transaction processing system that is accessible to the server 102 via the network 104. The network 104 can comprise a single network type or a combination of a plurality of network types, such as the Internet,

intranet, telephone system, satellite transmission, cable, fiber optic, etc. The network 104 can also support multiple protocol and interface types.

Also coupled to the server 102 via the network 104 is the receiver 106, such as a digital STB that communicates with the server 102 and displays data provided therefrom on the display device 108 (e.g., television screen, computer screen, etc.). This displayed data is then perceived by the viewer 110 who interacts with the receiver 106 using the input device 112, such as a remote control device, to affect the displayed data.

In order to facilitate the description of the invention, but without any loss in generality, this document will hereinafter disclose embodiments of the invention as they relate to cable television (TV) systems. Therefore, the viewer 110 views programs selected with the remote control device 112 on the TV screen 108. The program displayed on the TV screen 108 is rendered and displayed by the digital STB 106 that received the program data as a media stream from the video/audio server 102 via the hybrid fiberoptic/cable network 104. Elements of the media stream can include data provided by the data source 114 which is serving as a transaction processor on a web server coupled to the server 102 via the Internet.

In one embodiment and with reference to Figures 1 and 2, the server 102 transmits media streams comprising compressed digital programs and other data encoded in the MPEG-2 format to the digital STB 106 of the viewer 110. The media stream is transmitted in a 6 MHz channel as a multi-program transport stream (MPTS) that contains a plurality of digital MPEG programs. When the viewer 110 selects a program to view on a particular channel via the remote control device 112, the remote control

device 112 transmits a signal to an input element 230 of the digital STB 106. A processor 204 of the digital STB 106 executes an executable code 212 in a memory 210 of the digital STB 106 to tune a network interface 202 of the digital STB 106 to the desired 6 MHz channel. The network interface 202 of the digital STB 106 subsequently receives the media stream and obtains the desired digital program by parsing a specific single-program transport stream ("SPTS") from the MPTS. The SPTS corresponding to the desired program is then decoded by audio/video decoders 206 of the digital STB 106, rendered and subsequently displayed on the TV screen 108 via a display interface 240.

The delay time associated with channel tuning, MPTS parsing, and rendering accounts for much of the zap time (1-2 seconds) when switching channels. In some instances, where the desired program is not contained in the MPTS, the zap time increases (2-4 seconds) to accommodate the additional delay of informing the server 102 that a program is not available in the MPTS of the selected channel and for the server 102 to embed the SPTS associated with that program into the MPTS of the selected channel.

The invention uses the zap time introduced when switching channels to display a zap page 222 on the TV screen 108 of the viewer 110. Prior to receiving the channel-switch signal from the remote control device 112 at the input element 230, the zap page 222 is stored in a pre-rendered form (at least in part) in a frame buffer 220 of the digital STB 106. In response to the channel-switch signal or other zap event, the processor 204 executes the executable code 212 in memory 210 to transmit the zap page 222 in the buffer 220 to the display interface 240 for subsequent display on the TV screen 108. Once the zap page 222 has been transmitted, the executable code 212 renders a back-up

zap page 214 previously stored in the memory 210 and moves the newly-rendered, back-up zap page into the buffer 220 to await the arrival of a future zap event.

Referring to Figure 3, the zap page 222 displayed on the TV screen 108 in response to a zap event can comprise advertisement data 302, information about the target program 306 (e.g., its duration, actors, etc.), a window displaying the video of the target program 304 (such as may occur when the target program is available for display but has been temporarily suspended due to interactions with the zap page 222), an interactive element 308, and personal/local information 310. The zap page 222 is displayed on the TV screen 108, until the next/target program is ready for display, at which time, the target program moves to the foreground of the TV screen 108. However, display of the target program is suspended when the viewer 110 enters into an interactive session with the zap page 222. In any event, the viewer 110 can terminate the display of the zap page 222 at any time by pressing a button on the remote control device 112 that is perceived by the executable code 212 of the digital STB 106 as a zap termination event. When a zap termination event is received, the digital STB 106 displays the target program on the TV screen 108 even if it had been previously suspended.

The advertisement data 302 embedded in a particular zap page 222, can be determined in accordance with profile information gathered for the viewer 110. The profile information can be based on the viewer's prior TV viewing habits, prior purchasing habits, etc. The viewer's profile information can also be gathered by monitoring the viewer's activities and recording this data at the digital STB 106 or at the server 102. Alternatively or in combination, the server 102 can access the viewer's

profile information from the data source 114. For example, the data source 114 may contain the viewer's historical buying habits, usage rate of certain services, etc.

The interactive element 308 of the zap page 222 enables the viewer to interact with the zap page 222 to obtain additional information about objects displayed on the zap page 222 or to perform other actions related to these objects. For example, if the viewer 110 is viewing a product-related advertisement 302, the viewer may want to obtain the color options available for that product. The viewer 110 transmits a signal to the digital STB 106 using the remote control device 112 to request such data. The data request, performed while the zap page is being displayed, is referred to hereafter as a zap page request. The zap page request is received by the input element 230 and processed by the processor 204 and executable code 212. In this example, the executable code 212 may search the memory 210 or buffer 220 for the desired information.

If the information is not stored locally within the digital STB 106, the executable code 212 formulates a query that is transmitted by the network interface 202 to the server 102. The server 102, upon receipt of the query, accesses its internal data sources or external databases, web sites, etc. of the data source 114. Once the information is obtained, it is transmitted back to the requesting digital STB 106. The data source 114 can also provide access to a transaction processor hosted on a web server for placing orders, obtaining brochures, etc. In this manner, the viewer 110 can establish an interactive session with the remote data source 114 relating to interactive elements 308 available on the zap page 222.

While the viewer 110 is engaged in this interactive session, the display of the next/target program is suspended until the viewer 110 transmits a resume signal via the remote control device 112. The input element 230 of the digital STB 106 informs the executable code 212 that the resume signal has arrived, and the executable code 212
5 instructs the display interface 240 to move the next/target program to the foreground of the TV screen 108.

The personal/local information 310 displayed on the zap page 222 can also be based on the viewer's profile information and can be obtained from the digital STB 106, server 102 and/or data source 114. Examples of personal/local information include late-
10 breaking news stories, weather information, political information, current stock prices of securities held in the viewer's investment portfolio, arrival of electronic mail in the inbox of the viewer's email account, etc.

Referring to Figures 1, 2, and 4, the server 102 periodically transmits a plurality of zap page contents to the digital STB 106. The zap page contents can be formulated and
15 multicast by the server 102 to a plurality of end users or the zap page contents can be tailored and narrow cast to a particular viewer 110 based on that viewer's profile. When the executable code 212 determines that the zap page 222 in the buffer 220 has already or is currently being displayed on the TV screen 108 and that the back-up zap page 214 has been moved from the memory 210 and stored in a rendered form in the buffer 220 and a
20 new back-up zap page is therefore needed, the executable code 212 selects one of the plurality of zap pages (step 402) received at the network interface 202 of the digital STB 106. Once the zap page contents (that are in HTML format, for example) are selected

(step 402), the executable code 212 stores the zap page contents (step 404) in the memory 210 of the digital STB 106.

At some point, the viewer 110 transmits a signal to the input element 230 of the digital STB 106 indicative of the viewer's desire to switch channels. The input element 230 receives this channel-switch request (step 406) and informs the executable code 212 of this zap event. The executable code 212 instructs the display interface 240 to display the zap page 222 on the TV screen 108 (step 408) by moving the zap page 222 to the foreground of the TV screen 108. Assuming that the viewer 110 does not interact with the displayed zap page, the digital STB 106 completes its channel switching process to the target channel (step 416) and the program on the target channel is subsequently displayed on the TV screen 108 (step 418).

Alternatively, if the viewer 110 interacts with the displayed zap page 222, the input element 230 receives the zap page request (step 410) and informs the executable code 212 of its receipt. The executable code 212 continues with the switching process of the digital STB 106 but suspends the display of the target program (step 412). The executable code 212 then performs the zap page request (step 414) as previously discussed. When the zap page request has been fulfilled and/or a zap termination event is received by the digital STB 106, the switching process of the digital STB is completed for the target channel (step 416) and the target program is displayed (step 418) by bringing it to the foreground of the TV screen 108.

The zap page 222 is transmitted out of the buffer 220 in response to an appear event message issued by the zap page interaction process to the buffer 220 and is subsequently displayed on the TV screen 108. The zap page interaction process then issues a render event message that instructs the processor 204 and a rendering process to render the back-up zap page 214 and store it in the buffer 220 (step 514). In order to maintain a back-up zap page 214 in the memory 210, the zap page interaction process issues a fetch event message to the network interface 202 that selects a new back-up zap page from the available zap pages transmitted by the server 102 and stores the selected zap page as a new back-up zap page in the memory 210 of the digital STB 106 (step 516). In this manner, the zap page 222 can be displayed to the viewer 110 substantially immediately upon receipt of a zap event. Additionally, future zap events can be supported in rapid succession by continuously rendering and displaying the back-up zap page 214 and reacquiring a new back-up zap page when the prior back-up zap page 214 has been rendered.

Variations, modifications, and other implementations of what is described herein will occur to those of ordinary skill in the art without departing from the spirit and the scope of the invention as claimed. Accordingly, the invention is to be defined not by the preceding illustrative description but instead by the spirit and scope of the following claims.

What is claimed is:

Claims

1 1. A method of displaying data, comprising:

2 a) storing a first data set;

3 b) receiving a request to display a second data set;

4 c) receiving the second data set; and

5 d) transmitting the first data set during a delay period between receiving the
6 request and receiving the second data set.

1 2. The method of claim 1, wherein step a) comprises storing the first data set in a
2 buffer of a digital set top box.

1 3. The method of claim 1, wherein step b) comprises receiving a signal from a
2 television remote control device to switch channels, the signal corresponding to the
3 request to display the second data set, wherein the second data set corresponds to a
4 program associated with the switched channel.

1 4. The method of claim 1, further comprising the step of selecting the first data set
2 from a plurality of first data sets received over a network in accordance with profile
3 information.

1 5. The method of claim 4, further comprising the step of storing one of the plurality
2 of first data sets in a buffer of a digital set top box and storing another first data set in a

memory of the digital set top box, wherein the first data set in the memory of the digital set top box replaces the first data set in the buffer of the digital set top box once the first data set in the buffer is transmitted to a display device.

6. The method of claim 1, further comprising the step of displaying the first data set on a display device substantially upon receipt of the request for the second data set and terminating the display of the first data set upon initiating display of the second data set.

7. The method of claim 1, wherein the first data set comprises data associated with the second data set.

8. The method of claim 1, wherein the first data set comprises advertising data selected in accordance with a user profile.

9. The method of claim 1, further comprising the steps of:

- e) receiving an interactive request for additional data in response to the transmitted first data set; and
- f) transmitting the additional data to a display device.

10. The method of claim 9, further comprising the steps of:

- transmitting the interactive request to a data source, the data source having access to the additional data; and
- receiving the additional data from the data source.

1 11. The method of claim 9, further comprising the step of obtaining the additional
2 data from a local memory.

1 12. The method of claim 1, further comprising the steps of receiving a transaction
2 request associated with the first data set and transmitting the transaction request to a
3 transaction provider.

1 13. The method of claim 1, further comprising the steps of:
2 a) receiving a transaction request for additional data associated with the first data
3 set; and
4 b) displaying the additional data on a display device, wherein display of the
5 second data set on the display device is suspended until a resume signal is
6 received.

1 14. A system for displaying data, comprising:
2 a) a buffer for storing a first data set;
3 b) an input element for receiving a request for a second data set;
4 c) a network interface for receiving the second data set;
5 d) a display interface coupled to the buffer and to a display device for
6 transmitting data from the buffer to the display device;
7 e) memory storing an executable code; and

8 f) a processor for executing the executable code in response to the request
9 received by the input element, the executable code instructing the display
10 interface to transmit the first data set in the buffer to the display device during
11 a delay period between receiving the request and receiving the second data set.

1 15. The system of claim 14, wherein the first data set stored in the buffer corresponds
2 to a viewer of the display device.

1 16. The system of claim 14, wherein the network interface transmits the request for
2 the second data set to a remote data source.

1 17. The system of claim 14, wherein the request for the second data set corresponds to
2 a signal received from a television remote control device to switch channels, and wherein
3 the second data set corresponds to a program associated with the switched channel.

1 18. The system of claim 14, wherein the network interface receives a plurality of first
2 data sets and the executable code stores one of the plurality of first data sets in the buffer
3 and another of the first data sets in the memory, wherein the executable code replaces the
4 first data set in the buffer with the first data set in the memory once the first data set in the
5 buffer is transmitted to the display device.

1 19. The system of claim 14, wherein the display interface displays the first data set on
2 the display device substantially upon receipt of the second data set and terminates the
3 display of the first data set upon initiating display of the second data set.

1 20. The system of claim 14, wherein the first data set comprises data associated with
2 the second data set.

1 21. The system of claim 14, wherein the first data set comprises advertising data
2 selected in accordance with a viewer profile.

1 22. The system of claim 14, wherein the input element receives a transaction request
2 for additional data associated with the transmitted first data set and the display interface
3 displays the additional data on the display device until the input element receives a
4 resume signal.

USING DELAY TIME

Abstract of the Disclosure

During the several seconds of delay time that it takes for a digital set top box (“STB”) that is connected to a television or other display device to switch channels and display the next target program, other information or data can be displayed to a viewer of the television. This other data (“zap page”) can include, for example, advertising, information about the next/target program, a window showing a segment of the next/target program that is transmitted over the next/target channel, personal information associated with the viewer (e.g., notification that one or more electronic mail messages have arrived, stock prices of securities in the viewer’s portfolio, etc.) and potentially based on the viewer’s profile (e.g., recipes for cooking enthusiasts, news clips from preferred sources, advertisements of particular interest, etc.), and/or local and regional information (e.g., weather forecasts, etc.). The zap page also can include interactive elements that enable one-way and two-way transactions with the viewer. The zap page is pre-rendered and stored within the digital STB so that when the viewer requests a switch in channels, the zap page is displayed substantially immediately. The zap page is displayed until the channel switch has been completed and the next/target program is displayed. However, if the viewer engages in an interactive session, the display of the next/target channel is suspended until the viewer disengages the interactive session.

106




Fig. 2

400

Fig 5.

